





TILT TABLES

- Allows ergonomic access to components or baskets while reducing bending and back fatigue
- Can be stand alone or mounted to a table or scissor lift
- With 30°, 45° or 60° of tilt, our tilters are utilized in nearly any application
- Common applications include tote handling, bin handling, assembly applications and for positioning containers of small parts near assembly lines

PNEUMATIC TILTERS



HYDRAULIC SHOP AID SERIES TILTERS



A = Platform Width
 B = Platform Length
 C = Lowered Height

	LOAD CAPACITY (lbs.)	LOWERED HEIGHT (in.) (C)	TRAVEL	TILT STANDARD RETURN	PLATFORM DIMENSIONS (A X B) (in.)		LIFT SPEED (SECONDS)	STANDARD MOTOR (HP)	STANDARD VOLTAGE/ PHASE/HZ
					MINIMUM (W X L)	MAXIMUM (W X L)			
HYDRAULIC	30°								
	2000	10	30°	Gravity	24 x 36	60 x 60	11	1 (Internal)	115/1/60
	4000	10	30°	Gravity	24 x 36	60 x 60	15	1 (Internal)	115/1/60
	6000	10	30°	Gravity	24 x 36	60 x 60	20	1 (Internal)	115/1/60
	45°								
	2000	10	45°	Power	24 x 36	60 x 60	15	1 (Internal)	115/1/60
	4000	10	45°	Power	24 x 36	60 x 60	20	1 (Internal)	115/1/60
	6000	10	45°	Power	24 x 36	60 x 60	27	1 (Internal)	115/1/60
	60°								
2000	10	60°	Power	24 x 36	60 x 60	16	1 (Internal)	115/1/60	
4000	10	60°	Power	24 x 36	60 x 60	28	1 (Internal)	115/1/60	
6000	10	60°	Power	24 x 36	60 x 60	42	1 (Internal)	115/1/60	
PNEUMATIC	UP TO 40°								
	2000	8	40°	Gravity	30 x 48	60 x 54	N/A	N/A	N/A
	4000	8	40°	Gravity	48 x 48	72 x 54	N/A	N/A	N/A
	45°								
	2000	8	45°	Gravity	30 x 48	60 x 54	N/A	N/A	N/A
4000	8	45°	Gravity	48 x 48	72 x 54	N/A	N/A	N/A	

Platforms available in any dimension between minimums and maximums above